

DRYER driven by 4 electric motors														Aspirator engine power (Kw)	Scrapper engine power (Kw)	burner power min-max (Kw)	Burner models (Diesel/Lpg)
MODEL	Diameter (m)	Capacity (mc)	Capacity (t) specific weighth 0,75t/cm	Cylinder height with telescopic down, without top tube/with top tube down (m)	Height in work position without aspirator/ same with aspirator (m)	Discharge height without chute/with chute (m)	Single electric motor power (Kw)	Tractor nominal power 540rpm	Impellor motor power (Kw)/ increased	Main auger engine power (Kw)	Loading auger engine power (Kw)	Scrapper engine power (Kw)	Aspirator engine power (Kw)	burner power min-max (Kw)	Burner models (Diesel/Lpg)		
CPT 7/61 F	2,28	10	7,5	3,83/4,38	5,25/5,65	4,18	22	25	-	-	-	-	-	155-485	RL44/RS44		
CPT 10/77 T	2,28	13,5	10	3,88/4,38	5,06/5,95	4,14/3,67	22	25	-	-	-	-	-	148-593	RL50/RS50		
STR 9/87 F	2,45	12	9	3,97	3,97/5,18	2,9/2,41	30	37	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
STR 10/94 F	2,45	13	10	4,28	4,28/5,48	3,24/2,73	30	37	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
STR 11/100 F	2,45	14	10,5	4,48	4,48/5,68	3,44/2,93	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
STR 10/99 T	2,45	14	10	3,62/4,13	4,77/5,72	3,72/3,22	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
STR 13/119 T	2,45	17	13	4,02/4,55	5,48/6,68	4,38/3,91	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
FSN 11/103 F	2,65	15	11	4,28	4,28/5,41	3,1/2,64	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
FSN 12/110 F	2,65	16	12	4,48	4,48/5,68	3,37/2,9	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
FSN 13/127 T	2,65	18	13	3,62/4,13	5,06/6,27	3,96/3,48	30	40	11	15	7,5	2,2	1,5	255-830	RL70/RS70		
FSN 15/138 T	2,65	20	15	4,02/4,53	5,46/6,67	4,36/3,88	30	45	11/18,5	15	7,5	2,2	1,5	255-830	RL70/RS70		
FSN 15/138 T2	2,65	20	15	3,67/4,14	5,75/6,63	4,66/4,19	30	45	11/18,5	15	7,5	2,2	1,5	255-830	RL70/RS70		
D 14/125 F	3	19	14,5	4,5	4,5/5,7	4,23/2,78	30	45	15	15	7,5	2,2	1,5	255-830	RL100/RS100		
D 16/141 T	3	21,5	16	4,04/4,64	5,34/6,4	4,11/3,66	37	55	15/18,5	15	7,5	2,2	1,5	356-1186	RL100/RS100		
D 18/146 T	3	24	18	4,54/5,14	5,84/6,9	4,61/4,16	37	55	18,5	15	7,5	2,2	1,5	356-1186	RL100/RS100		
D 20/150 T LP	3	25	18	4,05/4,6	5,5/6,7	4,26/3,81	37	55	18,5/22	15	7,5	2,2	1,5	356-1186	RL100/RS100		
D 20/153 T HP	3	27	20,5	4,54/5,14	6,0/7,2	4,76/5,36	45	60	18,5/22	15	7,5	2,2	1,5	356-1186	RL100/RS100		
D 20/147 T2	3	27	20,5	4,1/4,64	6,2/7,05	4,96/4,51	45	60	18,5	15	7,5	2,2	1,5	356-1186	RL100/RS100		
D 24/175 T2	3	32	24	4,6/5,14	7,05/8,15	5,81/5,36	45	60	22	22	7,5	2,2	1,5	356-1186	RL100/RS100		
SSI 18/164 T	3,15	25	19	4,05/4,64	5,35/6,4	4,05/3,6	45	60	22	18,5	7,5	2,2	1,5	356-1186	RL100/RS100		
SSI 20/171 T	3,15	28	21	4,35/4,94	5,87/7,0	4,5/4,05	45	60	22	18,5	7,5	2,2	1,5	356-1186	RL100/RS100		
SSI 25/203 T2 LP	3,15	33	25	4,1/4,64	6,54/7,65	5,28/4,83	55	65	22	22	7,5	2,2	1,5	356-1186	RL100/RS100		
SSI 25/210T2	3,15	34	25	4,4/4,94	6,84/7,95	5,58/5,13	55	65	22	22	7,5	2,2	1,5	356-1186	RL100/RS100		
SSI 28/230 T2	3,15	38	28,5	4,4/4,94	7,2/8,35	5,93/5,48	55	75	30	22	7,5	2,2	1,5	356-1186	RL100/RS100		
S 34/255 T	3,85	43	32	4,67/5,33	6,37/7,79	4,74/4,21	75	75	30	22	11	2,2	2,2	486-1540	RL130/RS130		
S 34/263 F	3,85	44	33	6,38/6,38	6,38/7,79	4,55/-	75	75	30	22	11	2,2	2,2	486-1540	RL130/RS130		
S 35/280 T2	3,85	47	35	4,72/5,33	7,27/8,14	5,64/5,12	75	75	30	22	11	2,2	2,2	486-1540	RL130/RS130		
S 40/310 T2 LPC	3,85	52	39	4,72/5,33	7,47/8,39	5,84/5,32	75	85	37	30	11	2,2	2,2	486-1540	RL130/RS130		
S 43/340 T2 LPC	3,85	58	43,5	4,72/5,33	7,42/9,14	6,09/5,57	75	85	37	30	11	2,2	2,2	486-1540	RL130/RS130		
S 40/325 F	3,85	57	43	7,88	7,88/9,04	6/-	75	85	37	30	11	2,2	2,2	486-1540	RL130/RS130		
S 45/370 F	3,85	67	50	8,53	8,53/10	6,71/-	75	95	45	30	11	2,2	2,2	486-1540	RL190/RS190		
S 55/420 F(*)	3,85	75	56	9,66	9,66/10,9	7,79/-	55/45	110	55	37	11	2,2	3	600-2700	RL250/RS250		
F 75/570 (*)	4,5	97	75	11,05	11,05/11,5	8,1/-	75/45	130	75	-	-	-	3	710-3560	P300/GAS9		

Productivity T/days, at removal % humidity																
MODEL	electricity generator power (KVA)	Main impellor	Fan capacity (m3/h) at a pressure 200/100	Loading auger tube diameter (mm)	Main auger tube diameter (mm)	Tyres dimensions (two for one machine)	PTO driven Weight (Kg)*	PTO + 1 ME driven Weight (Kg)*	4 M.E. Driven Weight (Kg)*	1 M.E. driven or 2 M.E. driven (SF 55-F 75) Weight (Kg)*	25-14 Mais	25-14 Wheat	18-14 Soybean	25-14 Barley	14-8 Rapeseed	18-14 Rice
CPT 7/61 F	7	500/42	6500/15000	180	280	10,0/75-15,3 PR	2090	2470	/		45	43	55	36	38	26
CPT 10/77 T	7	500/42	9000/19000	180	280	10 5 FORI	2530	2910	/		57	55	70	45	46	36
STR 9/87 F	7	710/48	12500/32000	200	368		3200	3700	3500		60	58	74	48	50	38
STR 10/94 F	7	710/48	12500/32000	200	368		3200	3700	3500		65	65	82	53	53	41
STR 11/100 F	7	710/48	12500/32000	200	368		3350	3850	3650		70	67	86	55	57	46
STR 10/99 T	7	710/48	12500/32000	200	368	10,0/75-15,3 PR	3400	3900	3700		70	67	86	55	57	46
STR 13/119 T	7	710/48	20000/35000	200	368	12 6 FORI PTO -	3500	4000	3850		86	82	105	67	70	53
FSN 11/103 F	7	710/48	12500/32000	200	368	11,5/80-15,3 PR	3300	3800	3600		77	75	96	60	62	48
FSN 12/110 F	7	710/48	12500/32000	200	368	14 6 FORI 4 M.E.	3450	3950	3750		81	79	100	65	67	50
FSN 13/127 T	7	710/48	20000/35000	200	368		3500	4000	3800		91	86	110	72	74	57
FSN 15/138 T	7	710/48	26000/40000	200	368		3600	4100	3950		98	96	120	77	82	62
FSN 15/138 T2	7	710/48	26000/40000	200	368		3700	4200	4000		98	96	120	77	82	62
D 14/125 F	7	710/48	26000/40000	200	368		3500	4000	3800		96	91	117	74	79	60
D 16/141 T	7	710/48	26000/40000	200	368		3700	4150	3950		105	101	127	84	86	72
D 18/146 T	7	710/48	26000/40000	200	368	10,0/75-15,3 PR	3850	4300	4100		115	110	139	91	93	72
D 20/150 TLP	7	710/48	26000/40000	200	368	18 6 FORI PTO -	4050	4610	4400		117	120	153	98	101	79
D 20/153 T HP	7	710/48	26000/40000	200	368	11,5/80-15,3 PR	4100	4700	4500		120	122	154	101	103	81
D 20/147 T2	7	710/48	26000/40000	200	368	16 6 FORI 4 M.E.	4200	4800	4650		115	120	149	98	101	79
D 24/175 T2	7	710/48	26000/40000	200	368		4990	5550	5400	5200	127	130	173	108	118	91
SSI 18/164 T	7	800/55	26000/48000	200	368		5180	6070	5680		113	115	144	93	96	74
SSI 20/171 T	7	800/55	26000/48000	200	368		5280	6170	5780		127	125	155	100	105	81
SSI 22/180 T **	7	800/55	26000/48000	200	368		5370	6280	5870		130	127	158	103	108	84
SSI 25/203 T2 LP	7	800/55	36000/50000	200	368		5450	6340	5980		149	144	180	118	122	96
SSI 25/210 T2	7	800/55	45000/55000	200	368		5580	6470	6000		153	149	185	122	125	98
SSI 28/230 T2	7	800/55	45000/55000	200	368		5820	6740	6300		165	160	199	132	137	108
SSI 30/250 T2 **	7	800/55	45000/55000	200	368		6000	6840	6500		175	175	216	144	149	115
S 34/255 T	10	900/55	42000/62000	300	457	385/65-22,5 P27 8 FORI	7350	8270	7700	7500	199	194	242	158	163	127
S 34/263 F	10	900/55	42000/62000	300	457		7500	8550	8300		204	197	247	163	168	129
S 35/280 T2	10	900/55	42000/62000	300	457		7590	8350	8100		214	206	260	170	175	137
S 40/310 T2 LPC	10	900/55	60000/70000	300	457		7800	8600	8450		233	225	281	185	192	149
S 43/340 T2 LPC	10	900/55	60000/70000	300	457		7850	8750	8500	8585	249	252	314	206	214	165
S 40/325 F	10	900/55	60000/70000	300	457		7750	8700	8550		250	242	300	199	204	160
S 45/370 F	10	900/55	60000/70000	300	457		9900	10750	10500		283	276	338	225	233	182
S 55/420 F (*)	16	800 doppia	72000/100000	300	457		10500	11800	11000	10920	305	298	362	145	252	197
F 75/570 (*)	16	800 doppia	80000/110000	300	457		13700	14500	/	15100	403	377	456	310	320	252
												* Weight without aspiration system				

* Weight without aspiration system